

2012 FORD EDGE SPORT TECHNICAL SPECIFICATIONS

BODY	
Construction	Unibody
Final assembly location	Oakville Assembly Complex; Oakville, Ontario
POWERTRAIN AND CHASSIS	
ENGINE	
Type	3.7-liter 24-valve Ti-VCT V6
Manufacturing location	Lima Engine Plant; Lima, Ohio
Configuration	60-degree V6, aluminum block and heads
Intake manifold	Composite, split plenum
Exhaust manifold	Cast iron, true dual
Crankshaft	Forged steel
Redline	7,000 rpm
Idle speed in drive	600 rpm
Throttle body	65 mm, electronic
Valvetrain	DAMB, four valves per cylinder, intake variable camshaft timing
Valve diameter	Intake 37 mm, exhaust 31 mm
Pistons	High-temperature cast-aluminum alloy with low-friction coated skirts, low-tension rings
Connecting rods	Cracked powder metal
Ignition	Pencil coil
Bore x stroke	3.76 x 3.4 in./92.5 x 86.7 mm
Displacement	227.4 cu. in./3,731 cc
Compression ratio	10.5:1
Horsepower	305 @ 6,500 rpm (estimated)
Horsepower per liter	82.0
Torque	280 lb.-ft. @ 4,000 rpm (estimated)
Recommended fuel	87 octane (minimum)
Fuel capacity	18 gallons (FWD), 19 gallons (AWD)
Fuel injection	Sequential multiport fuel injection
Emission control	Closed loop with catalyst
Emissions (tailpipe/evaporation)	
Federal standards	Tier II/Bin 5, LEV II
California standards	ULEV II
Oil capacity	5.5 quarts, with filter
Recommended oil	GF4, 5W-20

2012 FORD EDGE SPORT TECHNICAL SPECIFICATIONS

DRIVETRAIN	
Layout	FWD (optional AWD)
TRANSMISSION	
Standard	Six-speed SelectShift Automatic™ with paddle activation
Gear ratios	
1st	4.48:1
2nd	2.87:1
3rd	1.84:1
4th	1.41:1
5th	1.00:1
6th	0.74:1
Reverse	2.88:1
Final drive	FWD 3.16, AWD 3.39
SUSPENSION	
Front	MacPherson strut and L-shaped lower control arm with isolated subframe and stabilizer bar
Rear	Independent with trailing blade, integrated knuckle and lateral links, isolated subframe and stabilizer bar
STEERING	
Type	Power hydraulic rack-and-pinion
Steering column	Tilt-telescope
Ratio	17.7:1 on center
Turns, lock-to-lock	3.1
Turning circle, curb-to-curb	38.6 ft.
BRAKES	
Type	Four-wheel ABS (four-channel); AdvanceTrac® with RSC® (Roll Stability Control™)
Front	Discs
Swept area	69.79 sq. in.
Rear	Discs
Swept area	70.12 sq. in.
Power assist	Yes
TIRES AND WHEELS	
	P265/40WR22 all-season BSW on 22x9-in. polished aluminum

DIMENSIONS (inches unless otherwise noted)	
EXTERIOR	
Wheelbase	111.2
Vehicle length	184.2
Vehicle width	76.0 (excluding mirrors), 87.5 (including mirrors)
Vehicle height without options	67.0

2012 FORD EDGE SPORT TECHNICAL SPECIFICATIONS

Track front/rear	65.4/65.2
Minimum running ground clearance	7.9
Approach angle	15.0 degrees
Departure angle	28.1 degrees
Ramp breakover angle	17.5 degrees
Cargo volume behind front row	68.9 cu. ft.
Cargo volume behind second row	32.2 cu. ft.
INTERIOR	
Seating capacity	Five
Headroom	
Front row	40.0
Second row	39.3
Legroom	
Front row	40.7
Second row	39.6
Shoulder room	
Front row	58.9
Second row	58.7
Hip room	
Front row	54.8
Second row	56.1
WEIGHTS AND CAPACITIES (pounds unless otherwise noted)	
Maximum towing capacity (when properly equipped)	2,000 (Class II)
Maximum payload (when properly equipped, including 150-pound driver)	
FWD	909
AWD	909
Base curb weight	
FWD	4,291
AWD	4,473
Weight distribution (front/rear)	60/40
FUEL ECONOMY	
FWD 3.7-liter V6	18 mpg city/25 mpg highway (estimated)
AWD 3.7-liter V6	17 mpg city/23 mpg highway (estimated)

Specifications subject to change